

COMBIFIX[®]-XL 8054 / 8098 / 8115

Fount concentrates for sheet-fed offset presses with continuous dampening systems

8054 09

for water with a bicarbonate content up to 250 mg/l

8054 19

for water with a bicarbonate content above 250 mg/l

Application

COMBIFIX-XL is intended for use on sheet-fed offset presses with continuous dampening systems, in combination with alcohol dosing systems. No more than 8 – 10 % isopropanol content is required.

Special properties

- Specific adjustment of surface tension
- Formation of a stable film of fount solution
- Very good protection of printing plates
- Meets corrosion standards - approved by press manufacturers

To adjust and stabilize the pH-value in the range between 5.0 and 5.3, considered most suitable for offset printing, two versions of COMBIFIX-XL are available to perfectly interact with your tap water. In case of doubt as to which product should be used, we are offering a free water analysis service.

Special versions

COMBIFIX-XL 8098 09 / 8098 19

With special additional ingredients to prevent roller-stripping

COMBIFIX-XL 811509 / 8115 19

Contains higher amounts of plate-protecting agents

Quantity to be added

The recommended addition is 4 %.

Labelling

Safety data sheet available on request.

How supplied

10-kg plastic containers
220-kg plastic drums
500-kg IBC