

SYSTEM CLEANER 8080 09

Cleaning concentrate for fount solution circulation systems

SYSTEM CLEANER is used for thorough cleaning of damping fount solution systems and fount application units with circulating systems. System Cleaner contains a combination of highly effective wetting and emulsifiers. It removes ink residue and dirt caused by the growth of microbes. System Cleaner is recommended for non-contacting spray and turbo systems as well as for contacting systems.

Application

It is recommended to include cleaning of the fount solution circulation systems in the machine maintenance programme at least once or twice a year.

Prior to using SYSTEM CLEANER, dilute it with water to a concentration of 5-7% depending on the degree of pollution. It is necessary to pump the cleaning solution through the supply system for 2-3 hours before flushing the system with water two or three times.

Homogenise SYSTEM CLEANER by shaking the container before using it.

Special Properties

- Highly active wetting agents dissolve contamination and persistent ink residues adhering to the walls of the piping system.
- Emulsifiers dissipate contamination uniformly in the cleaning solution.
- SYSTEM CLEANER does not attack metals or plastic materials.

Precautionary Measures

We recommend to wear protective gloves and goggles (eye-protection against splashes) when handling this concentrate like with any other chemical, too.

Labelling

Safety data sheet available on request.

How Supplied

10-kg plastic containers